

# BARDOLINE® CLASSIC TRADITIONAL

## TECHNICAL DATA SHEET

### MATERIAL / APPLICATION

BARDOLINE® CLASSIC TRADITIONAL is a colored bitumen shingle with thermoadhesive points for roof and wall covering.



BARDOLINE® CLASSIC TRADITIONAL is manufactured in conformity with ETA 07/0266

### TECHNICAL CHARACTERISTICS

Length	1000 mm	+/-5	EN 544
Width	336 mm	+/-3	EN 544
Thickness	3 mm	+/-5%	
Exposed area	144 mm		
Min./max. pitch	15° - 60°*		


\* Valid for I. and II. snow zone. For III. and more, please add 5°

### Product performance

Weight	9.2 kg/m <sup>2</sup>	+/-10%	
Mass of the fibreglass mat	100 g/m <sup>2</sup>	+/-10%	
Granules single layer	>11 0 g/m <sup>2</sup>		
Mechanical resistance MD/CMD	>600/400 N/5 cm		EN 544
Nail shrank resistance	>100 N		EN 544
Granules adhesion	<1.2 g		EN 544

### Fire behaviour

External fire performance: classification according	F roof	EN 13501-5
Reaction to fire: classification according	E	EN 13501-1



### COLOR RANGE




### PACKAGING

Type	Polyethylene
Shingles per bundle	21
Bundle per pallet	51
m <sup>2</sup> /bundle	3 m <sup>2</sup>
m <sup>2</sup> /pallet	153 m <sup>2</sup>

### HANDLING AND STORAGE

BARDOLINE® CLASSIC TRADITIONAL should be kept under dry conditions, protected from UV and heat as well as rain and moisture.



### APPLICATION AND WARRANTY

All the claims will be considered with respect to application recommendations issued by Onduline company.

The printed colours differ slightly from the true colours. We recommend that you visit our authorised dealerships to view the products of this document in person.

This document was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is consumer responsibility to use the product in accordance to producer/distributor recommendations and his needs.

### ONDULINE AVRASYA

Değirmen Sokak Nida Kule İş Mrk.  
No:18 Kat:8 34742 Kozyatağı, Kadıköy/ İSTANBUL / TURKEY  
Tel: +90 216 384 16 00 pbx.  
Fax : +90 216 384 16 10  
www.onduline.com.tr

**Onduline®**