


# BARDOLINE® CLASSIC NOVA

## TECHNICAL DATA SHEET

### MATERIAL / APPLICATION

BARDOLINE® CLASSIC NOVA is a colored bitumen shingle for roof and wall covering with thermoadhesives tabs. Protective microfilm should be mechanically removed before application.



BARDOLINE® CLASSIC NOVA has CE mark and is manufactured in conformity with ETA - 07/0266

### TECHNICAL CHARACTERISTICS

Length	1000 mm	+/-3	EN 544
Width	336 mm	+/-3	EN 544
Thickness	3 mm	+/-10%	
Exposed area	133 mm		
Min./max. pitch	15° - 60°*		

\* Valid for I. and II. snow zone. For III. and more, please add 5°


### Product performance

Weight	7.35 kg/m <sup>2</sup>	+/-10%	
Mass of the fibreglass mat	100 g/m <sup>2</sup>	+/-10%	
Mass of bitumen	>1300 g/m <sup>2</sup>		EN 544
Granules single layer	>1200 g/m <sup>2</sup>		
Mechanical resistance MD/CMD	>600/400 N/5 cm		EN 544
Nail shrank resistance	>100 N		EN 544
Granules adhesion	2.5 g		EN 544
Minimum adhesion temperature for tabs	60 °C		

### Fire behaviour

External fire performance: classification according	B roof (t1)	EN 13501-5
Reaction to fire: classification according	E	EN 13501-1

### COLOR RANGE




DUAL RED DUAL BROWN DUAL GREY DUAL GREEN

### PACKAGING

Type	Polyethylene
Shingles per bundle	22
Bundle per pallet	45
m <sup>2</sup> /bundle	3
m <sup>2</sup> /pallet	135

### HANDLING AND STORAGE

BARDOLINE® CLASSIC NOVA should be kept under dry conditions, protected from UV and heat as well as rain and moisture.



### APPLICATION AND WARRANTY

All the claims will be considered with respect to application recommendations issued by Onduline company.

The printed colours differ slightly from the true colours. We recommend that you visit our authorised dealerships to view the products of this document in person.

This document was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is consumer responsibility to use the product in accordance to producer/distributor recommendations and his needs.

### ONDULINE AVRASYA

Değirmen Sokak Nida Kule İş Mrk.  
No:18 Kat:8 34742 Kozyatağı, Kadıköy/ İSTANBUL / TURKEY  
Tel: +90 216 384 16 00 pbx.  
Fax : +90 216 384 16 10  
www.onduline.com.tr